



Lightweight wrap-around style safety spectacle.

KEY FEATURES

- Close-fitting protection
- Universal nose bridge
- Wide field of vision
- Weight: 25g
- Optical class 1 polycarbonate lens



ORDERING INFORMATION

VERSIONS	REF.	LENS MARKING	FRAME MARKING	PROTECTION AGAINST	COATINGS
CLEAR	 RLYB0011	2C-1.2 e 1FT CE	e EN 166 FT CE	Impacts, UV radiations	Anti-scratch
DK GREY	 RLYB0013	5-3.1 e 1FT CE	e EN 166 FT CE	Impacts, UV and Solar radiations	



GENERAL SPECIFICATIONS

LENS BASE	10mm
WEIGHT	25g

PACKAGING

Individually contained in a polythene bag with a Euroslot

PER BOX	10
PER CARTON	200

COMPONENT SPECIFICATION

COMPONENT	MATERIAL	FEATURES
LENS AND NOSEBRIDGE	Polycarbonate	Single piece, moulded
TEMPLE	Polycarbonate	Robust and durable
HINGE	Stainless steel	Hard wearing


LENS MARKINGS

LENS FILTER TYPE:

- 2C** UV
- 5** Solar

SCALE NUMBER (SHADE):

- 1.2** Clear
- 3.1** Dark Grey

 Identity of the manufacturer

OPTICAL CLASS:


- 1** High optical quality

MECHANICAL STRENGTH:

- F** Low energy impact, resists a 6mm, 0.86g ball at 45m/s
- T** Protection against high-speed particles at extreme temperatures

 Certification mark

FRAME MARKINGS

 Identity of the manufacturer

EN 166: guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

MECHANICAL STRENGTH:

- F** Low energy impact, resists a 6mm, 0.86 g ball at 120m/s
- T** Protection against high-speed particles at extreme temperatures
- CE** Certification mark

CLEANING AND STORAGE

CLEANING: The lenses should be cleaned regularly.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfibre pouch or rigid case.

STORAGE: All products must be stored in a dry and clean environment.