



Lightweight wrap-around style safety spectacle.

KEY FEATURES

- ▶ Integral lateral protection
- ▶ 3-position length adjustment
- ▶ Soft comfort ventilated nose pads
- ▶ Soft temple ends
- ▶ Interchangeable lens functionality
- ▶ Weight: 22g
- ▶ Optical class 1 polycarbonate lens



CLEAR



GREY

ORDERING INFORMATION

VERSIONS	REF.	LENS MARKING	FRAME MARKING	PROTECTION AGAINST	COATINGS
CLEAR	BM04CLR	2C-1.2 ▶ 1FT CE	▶ EN 166 FT CE BM04	Impacts, UV radiations	Anti-scratch
	BM04CLRAF				Anti-scratch+anti-fog
GREY	BM04GRY	5-2.5 ▶ 1FT CE	▶ EN 166 FT CE BM04	Impacts, UV and Sun Glare	Anti-scratch



GENERAL SPECIFICATIONS

LENS BASE	9.5mm
WEIGHT	22g

PACKAGING

Individually contained in a polythene bag with a Euroslot

PER BOX	10
PER CARTON	200

COMPONENT SPECIFICATION

COMPONENT	MATERIAL	FEATURES
LENS AND NOSEBRIDGE	Polycarbonate	
TEMPLE	Polycarbonate	Robust and durable
HINGE	Stainless steel	Hard wearing

LENS MARKINGS

LENS FILTER TYPE:

- 2C UV
- 5 Solar

SCALE NUMBER (SHADE):

- 1.2 Clear
- 2.5 Grey

- Identity of the manufacturer

OPTICAL CLASS:

- 1 High optical quality

MECHANICAL STRENGTH:

- F Low energy impact, resists a 6mm, 0.86g ball at 45m/s
- T Protection against high-speed particles at extreme temperatures

- CE Certification mark

FRAME MARKINGS

- Identity of the manufacturer

EN 166: guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

MECHANICAL STRENGTH:

- F Low energy impact, resists a 6mm, 0.86g ball at 45m/s
- T Protection against high-speed particles at extreme temperatures
- CE Certification mark

CLEANING AND STORAGE

CLEANING: The lenses should be cleaned regularly.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfibre pouch or rigid case.

STORAGE: All products must be stored in a dry and clean environment.