



Over spectacle.

KEY FEATURES

- ▶ Brow protection
- ▶ Ventilated temples
- ▶ Anti-scratch lens
- ▶ Lateral protection
- ▶ Ideal to be worn by site visitors
- ▶ Weight: 45g
- ▶ Optical class 1 polycarbonate lens
- ▶ Metal free



ORDERING INFORMATION

VERSIONS

CLEAR

REF.

RLYB0031

LENS MARKING

2C-1.2 e 1FT CE

FRAME MARKING

e EN 166 FT CE

PROTECTION AGAINST

Impacts, UV radiations

COATINGS

Anti-scratch



GENERAL SPECIFICATIONS

LENS BASE	4mm
WEIGHT	45g

PACKAGING

Individually contained in a polythene bag with a Euroslot

PER BOX	10
PER CARTON	200

COMPONENT SPECIFICATION

COMPONENT	MATERIAL	FEATURES
LENS AND NOSEBRIDGE	Polycarbonate	Single piece, moulded with side protection
TEMPLE	Polycarbonate	Robust and durable
HINGE	Polycarbonate	Metal-free

LENS MARKINGS

LENS FILTER TYPE:
2C UV

SCALE NUMBER (SHADE):
1.2 Clear

 Identity of the manufacturer

OPTICAL CLASS:
1 High optical quality

MECHANICAL STRENGTH:
F Low energy impact, resists a 6mm, 0.86g ball at 45m/s
T Protection against high-speed particles at extreme temperatures

 Certification mark

FRAME MARKINGS

 Identity of the manufacturer

EN 166: guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

MECHANICAL STRENGTH:
F Low energy impact, resists a 6mm, 0.86g ball at 45m/s
T Protection against high-speed particles at extreme temperatures

 Certification mark

CLEANING AND STORAGE

CLEANING: The lenses should be cleaned regularly.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfibre pouch or rigid case.

STORAGE: All products must be stored in a dry and clean environment.