



Lightweight wrap-around style safety spectacle.

KEY FEATURES

- ✔ Soft comfort nose pads
- ✔ 3 point lens tilt adjustment
- ✔ Thin, flexible nylon temples provide non-pressure fitting
- ✔ Ventilated temple tips
- ✔ Weight: 23g
- ✔ Optical class 1 polycarbonate lens



ORDERING INFORMATION

VERSIONS	REF.	LENS MARKING	FRAME MARKING	PROTECTION AGAINST	COATINGS
CLEAR	BM12CLR	2C-1.2 ▶ 1F CE	▶ EN 166 F CE BM12	Impacts, UV radiations	Anti-scratch
	BM12CLRAF				Anti-scratch+anti-fog
GREY	BM12GRY	5-2.5 ▶ 1F CE	▶ EN 166 F CE BM12	Impacts, UV and Sun glare	Anti-scratch



GENERAL SPECIFICATIONS

LENS BASE	9mm
WEIGHT	23g

PACKAGING

Individually contained in a polythene bag with a Euroslot

PER BOX	10
PER CARTON	200

COMPONENT SPECIFICATION

COMPONENT	MATERIAL	FEATURES
LENS AND NOSEBRIDGE	Polycarbonate	Single piece, moulded
TEMPLE	Transparent nylon	Resilient and pressure free
HINGE	Stainless steel	Hard wearing

LENS MARKINGS

LENS FILTER TYPE:

- 2C UV
- 5 Solar

SCALE NUMBER (SHADE):

- 1.2 Clear
- 2.5 Grey

- Identity of the manufacturer

OPTICAL CLASS:

- 1 High optical quality

MECHANICAL STRENGTH:

- F Low energy impact, resists a 6mm, 0.86g ball at 45m/s

- CE Certification mark

FRAME MARKINGS

- Identity of the manufacturer

EN 166: guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

MECHANICAL STRENGTH:

- F Low energy impact, resists a 6mm, 0.86g ball at 45m/s

- CE Certification mark

CLEANING AND STORAGE

CLEANING: The lenses should be cleaned regularly.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfibre pouch or rigid case.

STORAGE: All products must be stored in a dry and clean environment.